

Toter®

Built for Extremes™

LIFTERS



MOBILE LIFTERS

Mobile lifters allow for flexibility in tight quarters or dumping into multiple locations. When not in use, they roll to store away easily. Unit ships standard with indoor/outdoor battery charger and deep cycle 12-volt battery.



ATLAS (3081 SERIES MT)

Our Atlas lifter is designed to dump 2-wheel caster carts as well as Toter Atlas 32- and 44-gallon containers, and most competitive barrel-style containers with side lift handles. Dumps into stationary and self-contained compactors, front or side load containers, roll-off open top containers, through-wall compactor chutes, etc.

Part	Base Dimensions w/out chute	Load Rating	Dump Height	Power Supply
3081-MT-1000	53.50" x 35.00" x 43.00"	350 lbs	68.00" – 84.00"	12 volt battery (DC)



Saddle (3081 SERIES MT)

The Saddle Lifter is designed to work with Toter 32/48/64/96 gallon two-wheel and caster carts only.

Part	Base Dimensions w/out chute	Load Rating	Dump Height	Power Supply
3081-MT-5000	53.50" x 35.00" x 43.00"	350 lbs	50.00" – 84.00"	12 volt battery (DC)

Rover (3063 SERIES MT)

The Rover provides a greater range of dump height options. Also available for this unit as an add-on option: 3063-MT-6008 Auto-lock Hydraulic System for increased stability when dumping on uneven surfaces. Lifter is designed to work with Toter 32/48/64/96 gallon two-wheel and caster carts only.



Part	Dimensions	Load Rating	Dump Height	Power Supply
3063-MT-4018	Dimensions depend on model	350 lbs	41.50" – 43.50"	12 volt battery (DC)
3063-MT-4020	Dimensions depend on model	350 lbs	45.50" – 47.50"	12 volt battery (DC)
3063-MT-4022	Dimensions depend on model	350 lbs	49.50" – 51.50"	12 volt battery (DC)
3063-MT-4024 Towable	Dimensions depend on model	350 lbs	53.50" – 55.50"	12 volt battery (DC)
3063-MT-4124 Non-towable	Dimensions depend on model	350 lbs	53.50" – 55.50"	12 volt battery (DC)
3063-MT-4126	Dimensions depend on model	350 lbs	57.50" – 59.50"	12 volt battery (DC)
3063-MT-4128	Dimensions depend on model	350 lbs	61.50" – 64.50"	12 volt battery (DC)
3063-MT-4132	Dimensions depend on model	350 lbs	69.50" – 74.50"	12 volt battery (DC)

Note: Dump height varies depending upon size of container being used. Rover lifters are available in a variety of additional dump heights as a special order. Towable Rover must be used with Pintle Hook Tow Hitch.



Economy (3069 SERIES MT)

Our most economically designed lifter is designed to work with Toter 32/48/64/96 gallon two-wheel and caster carts only.

Part	Dimensions	Load Rating	Dump Height	Power Supply
3069-MT-2000	39.00" x 48.00" x 46.50"	350 lbs	48.00"	12-volt battery (DC)



NEW! Global Dumper (3065 CS SERIES MT)

The Global Dumper handles all ANSI Standard & D.I.N. Euro Standard carts from 32 to 96 gallons. Works with two-wheel carts and caster carts.

Part	Dimensions	Load Rating	Dump Height	Power Supply
3065-CS MT	N/A	350 lbs	48.00"	208/230/460/600V single or three phase, 5 HP

MOUNTED LIFTER SOLUTIONS

Truck, compactor, bailer, stand or wall mounted lifters are designed to reduce back injuries wherever permanent mounting is needed.



Trim Lifter (3063 SERIES)

The Trim Lifter handles Toter cans from 32 to 96 gallons. Works with two-wheel carts and caster carts.

Part	Dimensions	Load Rating	Dump Height	Power Supply
3063-TL	39.00" x 48.00" x 46.50"	350 lbs	Varies	PTO-Driven

NEW! Swing-Away Lifter (3079 SERIES)

The Swing-Away is a double-lifter unit that is hung on a swinging-gate frame and handles Toter cans from 32 to 96 gallons. Works with two-wheel carts and caster carts and 1 yard mobile trucks.

Part	Dimensions	Load Rating	Dump Height	Power Supply
3079-SR or SL	Dimensions depend on model	Up to 2,000 lbs	37"	208/230/460/600V single or three phase, 5 HP

STATIONARY LIFTERS

Stationary lifters are designed for permanent mounting into concrete or metal pad. Control options include manual or push-button controls.



Stand Mount (3063 SERIES ST)

Actuator operated with more versatile dump height options allows you to dump Toter 32/48/64/96 gallon two-wheel and caster carts only.

Part	Dimensions	Load Rating	Dump Height	Power Supply
3063-ST-4124	N/A	350 lbs	49.50" – 54.00"	115/230V single phase, 2 HP
3063-ST-4324	N/A	350 lbs	49.50" – 54.00"	208/230/460V three phase, 2 HP
3063-ST-4126	N/A	350 lbs	52.50" – 58.00"	115/230V single phase, 2 HP
3063-ST-4326	N/A	350 lbs	52.50" – 58.00"	208/230/460V three phase, 2 HP
3063-ST-4128	N/A	350 lbs	57.50" – 62.00"	115/230V single phase, 2 HP
3063-ST-4328	N/A	350 lbs	57.50" – 62.00"	208/230/460V three phase, 2 HP
3063-ST-4132	N/A	350 lbs	65.50" – 70.00"	115/230V single phase, 2 HP
3063-ST-4332	N/A	350 lbs	65.50" – 70.00"	208/230/460V three phase, 2 HP



Atlas (3081 SERIES ST)

The Atlas lifter is designed to dump 2-wheel and caster carts as well as Toter Atlas 32- and 44-gallon containers, and most competitive barrel-style containers with side lift handles. Dumps into stationary and self-contained compactors, front or side load containers, roll-off open top containers, through-the-wall compactor chutes, etc.

Part	Dimensions	Load Rating	Dump Height	Power Supply
3081-ST-1000	53.50" x 35.00" x 43.00"	350 lbs	68.00" – 84.00"	115/230/480V single phase and three phase, 1 - 3HP



Saddle (3081 SERIES ST)

The Saddle lifter dumps Toter 32/48/64/96 gallon 2-wheel and caster carts. Dumps into stationary and self-contained compactors, front or side load containers, roll-off open top containers, through-the-wall compactor chutes, etc.

Part	Dimensions	Load Rating	Dump Height	Power Supply
3081-ST-5000	N/A	350 lbs	68.00" – 84.00"	115/230/480V single phase and three phase, 1 - 3HP



Candy Cane (3064 SERIES ST)

The Candy Cane ability to dump high (120 inches) and deep into a hopper comes in handy for those who deal in bulk amounts of waste and materials. Works with Toter two-wheel carts and caster carts.

Part	Dimensions	Load Rating	Dump Height	Power Supply
3081-ST-5000	N/A	350 lbs	72.00" – 120.00"	208/230/460V single or three phase, 2 HP & 3 HP



Universal / Pan Lifter / Box Dumper (3078 SERIES ST)

Available as a fork or pan lifter. These double-cylinder units can dump from a 32-gallon can to a 4 cubic yard container. Do you have a non-standard container? We will customize this unit to fit your needs.

Part	Dimensions	Load Rating	Dump Height	Power Supply
3078-LP-5000	N/A	2,500 lbs	30.00"	208/230/460/600V single or three phase, 5 HP
3078-XX-6000	N/A	2,500 lbs	48.00" – 70.00"	208/230/460/600V single or three phase, 5 HP
3078-BD-7000	N/A	2,500 lbs	48.00" – 65.00"	208/230/460/600V single or three phase, 5 HP



Twin Post High Lift (3077 SERIES ST)

Our most versatile unit is available as a fork or pan lifter. Customizable to dump two units at once, it is also our highest reaching lifter going from 4 feet to 20 feet. This unique unit can dump from a 32 gallon can to a 4 cubic yard container. Do you have a non-standard container? We will customize this unit to fit your needs.

Part	Dimensions	Load Rating	Dump Height	Power Supply
3077-00-3000	N/A	Up to 3,000 lbs	48.00" – 240.00"	208/230/460/600V single or three phase, up to 10 HP



NEW! Global Dumper (3065 CS SERIES ST)

The Global Dumper handles all ANSI Standard cans from 32 to 96 gallons. Works with two-wheel carts and caster carts.

Part	Dimensions	Load Rating	Dump Height	Power Supply
3065-CS ST	N/A	350 lbs	48.00"	208/230/460/600V single or three phase, 5 HP

LIFTER SAFETY SOLUTIONS AND ACCESSORIES

Our base-lifters are designed with safety and ergonomics in mind. They're customizable to meet your requirements; from food grade to outdoor-use. We build lifters to suit your needs.

Options

- Limit switches
- Flashing light w/horn
- Safety cages
- Auto-lock system
- Palm buttons
- Timers
- Floor stop
- Manual hand-valve controls
- Electrical push-button controls
- PLC controls (programmable logic controller)
- Key locked controls
- Multi-color paint palette
- Stainless steel food-grade units
- Horsepower ranges from 1HP to 10HP
- Voltage ranges from 12V to 600V
- Single-phase or three phase

Power Units and Controls



Operator Controls



Control Panel



Manual Valve Controls



Power Unit

Power units available to fit your current electrical requirements from single to three phase, from 115 to 600 volts.



Batteries and Battery Box
All are shipped with a 12-volt power unit and battery. An optional 12-volt battery charger is available.



Auto-lock System

All auto lock system uses cylinders to lift the unit in use, so the unit does not move during operation.

Extreme Purpose • Extreme Toughness • Extreme Wear



Toter[®]

Built for Extremes[™]